

ACP-2010MB / 2320MB

2U Rackmount Chassis for ATX/ MicroATX Motherboard with Low-Profile Rear Bracket Option



Features


- LED indicators and audible alarm notification for system fault detection
- Shock-resistant drive bays to hold one 5.25" and three 3.5" drives for ACP-2010MB (one front-accessible and two internal); one slim optical disk drive, two internal 3.5" drives and dual mobile SAS/SATA HDD trays for ACP-2320MB
- Various riser card options to support three full-size PCI or PCIe cards for expansion
- Supports 300W / 400W ATX PFC power supply
- Reusable and washable air filters



Specifications


		Front-accessible	Internal
Drive Bay	Slim Optical Disk Drive	- / 1	-
	5.25"	1 / 0	-
	3.5"	1 / 2 SAS/SATA HDD (mobile trays compatible with 2.5" HDD/SSD)	2 / 2
Cooling	Fan	2 (8 cm /47 CFM each) / 2 (8 cm /47 CFM each) + 1 (6 cm /28 CFM) for SAS/SATA storage unit	
	Air Filters	Yes	
Front I/O Interface	USB	2	
	PS/2	1	
Miscellaneous	LED Indicators	Power, HDD, temperature, fan	
	Rear Panel	Two 9-pin D-Sub openings	
Environment	Temperature	Operating 0 ~ 40° C (32 ~ 104° F)	Non-operating -20 ~ 60° C (-4 ~ 140° F)
	Humidity	10 ~ 85% @ 40° C, non-condensing	
	Vibration (5 ~ 500 Hz)	1 Grms	
	Shock	10 G (with 11 ms duration, half sine wave)	
	Shock	30 G	
Physical Characteristics	Dimensions (W x H x D)	482 x 88 x 480 mm (19" x 3.46" x 18.9")	
	Weight	10.7 kg (23.5 lb) / 11.7 kg (25.7 lb)	

Front View




ACP-2010MB

Inside View




ACP-2010MB

Rear View



ACP-2320MB



ACP-2320MB


Rear I/O bracket for low profile add-on cards




Dimensions

Unit: mm [inch]

ACP-2010MB



ACP-2320MB



Ordering Information

Part Number	Power Supply
ACP-2010MB0-00XBE	Without power supply, with ATX switch
ACP-2320MB0-00XBE	Without power supply, with ATX switch

Power Supply Options

(For detailed power supply specs, please refer to Chapter 13)

Part Number	Specifications	
	Watts	Input
1757000007G (ATX, PFC)	300W	AC 100 ~ 240 V (full range)
1757000105G (ATX, PFC)	400W	AC 100 ~ 240 V (full range)
1757001137 (ATX, PFC) (1+1 redundant)	250W	AC 100 ~ 240 V (full range)

Optional Accessories

Part Number	Description
Rear I/O panel kit for low-profile add-on cards	
1939000361	Screw (should purchase 7 pcs)
1960034816N000	I/O bracket (should purchase 7 pcs)
1960019475T201	Rear panel for low-profile
1950014302N001	Special bracket for riser card AIMB-RP3P8-12A1E
96CB-SATAPOWER-6P1	SATA power wire 6-pin to big 4-pin (for slim ODD)
IDT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays

Spare Parts

Part Number	Description
9662132020E	Black mobile HDD tray
1990007986S000	Door filter 156 x 45 x 5 mm
1990001949	Fan filter bracket 168 x 58 mm