

# Advantech Automation Panel

Next-Generation Human Machine Interface  
with True Flat Touch and Intelligent Keys



- Introduction
- Features & Functions
- Intelligent Software
- Selection Guide



**ADVANTECH**

*Enabling an Intelligent Planet*

[www.advantech.com](http://www.advantech.com)



# Advantech Automation Panels

Next-Generation Human Machine Interface  
with True Flat Touch and iKeys

## 16:9 Wide Screen Format with Multi Touch

The 16:9 widescreen format increases the viewing area by 40% compared to traditional 4:3 displays, thereby enhancing the management and display of information. The integration of multi-touch functionality enhances operational safety by enabling two-point key confirmation.



## Magnesium Alloy Front Panel

Advantech's 18.5/21.5" automation panel computers that feature a magnesium alloy front panel weigh 35% less than the aluminum alloy models.



## IP66-Rated True Flat Touchscreen

In addition to IP66 certification for dust and water resistance, Advantech's automation panel computers feature a true flat P-CAP/resistive touch screen with an anti-scratch surface of 7H hardness to prevent accidental scratches due to extreme handling.



## Easy Installation

Equipped with a unique snap design, Advantech's automation panel computers can be installed by a single person, thereby speeding up the installation process.



## Intelligent Keys and Customizable UI

With the inclusion of intelligent keys, Advantech's TPCs provide an intuitive GUI that saves time by simplifying operations. Customers can easily customize their UI using the updated SDK and APIs available on Advantech's website.



## Boot on Touch Capability

Advantech's touch panel PCs support boot-on-touch functionality for easy and convenient operation.



## Supports VESA Arm Mount

With support for a standard 100 x100 mm VESA arm mount, Advantech's SPC are suitable for diverse applications, such as automobile production operations.




Advantech's new Automation Panel Computer include several new models in the Touch Panel Computer(TPC), Stationary Panel Computer(SPC) and Industrial Monitor(FPM) range of devices, all of which come with true flat style by 16:9 multi-touch displays or 4:3 5W resistive touch, high-performance Multi-core processors and IP66 certified front panels making them more elegant and fit for smart factory. Furthermore, Automation Panels integrated several S/W solution to empower applications and fit to the IIoT era, make the solutions with high efficiency, reduce the cost of production and provide factory workers with more intuitive management of the production line.



**Multiple I/Os with M12 Connector**

Advantech's SPC computers offer diverse I/O, including COM, USB, 1000 Base-T LAN, HDMI, Audio In, and M12 connection ports.



**Supports iDoor Technology**

With Advantech's iDoor technology, customers can integrated peripherals and expand the system functions via the diverse I/O. The iDoor modules available include a Fieldbus protocol, memory expansion and storage, digital and analog I/O, WAN, Wi-Fi-based MAN and LAN communication, GPS, GPRS, and LTE modules.

**Stainless Steel Unit with IP69K Rating**

The stainless steel unit housing with IP69K certification ensures ease of maintenance and cleaning, making the device suitable for use in hospitality, clinical, and pharmaceutical laboratory applications.



**Fanless Intel® Core™ i CPU**

Equipped with a powerful CPU processor, Advantech's automation panel computers offer advanced computing and graphics performance for computationally intensive processes.

# Intelligent Software

## Advantech WebAccess

## WebAccess/SCADA

Advantech WebAccess is a 100% web-based SCADA software platform that provides open interfaces for developing IIoT applications aimed at various vertical markets. WebAccess features an intelligent dashboard that offers cross-platform, cross-browser data analysis and an intelligent UI using HTML5 technology. WebAccess also supports Widget Builder, which allows customers to build their own widgets.



## Wise-PaaS/RMM

## WISE-PaaS/RMM

As part of Advantech’s WISE-PaaS cloud solution, WISE-PaaS/RMM enables remote device management and monitoring by providing centralized management features, including HW/SW status monitoring and remote device control. WISE-PaaS/RMM utilizes the standard IoT protocol (MQTT) to communicate with IPCs, IoT gateways, and sensors to thereby provide the WISE Agent framework for data acquisition. Additionally, WISE-PaaS/RMM supports RESTful API web service, allowing users to integrate RMM functions with other applications.

## WebAccess/HMI

## WebAccess/HMI

WebAccess/HMI is a powerful and intuitive software platform for creating total HMI solutions for diverse application fields. As an easily integrated development tool, WebAccess/HMI guarantees reliability and open access due to minimal system overheads, high data communication rates, sub-second screen switching capability, and capacity for 24/7 operation.



Data Collection



Unlimited Internal Points



450 Protocols



Over 50 Screen Objects



Supports 16 Communication Links

# Selection Guide



Model	TPC-1251T/1551T	TPC-1051WP/1551WP	TPC-1581WP/1881WP	SPC-1881WP/2140WP	IPPC-5211WS	FPM-7151W/7181W/7211W	
<b>Category</b>	Touch Panel Computer	Touch Panel Computer	Touch Panel Computer	Stationary Panel Computer	Touch Panel Computer	Industrial Monitor	
<b>Aspect Ratio</b>	4:3			16:9			
<b>CPU</b>	Intel® Atom™ E3827 (1.75 GHz) processor	Intel® Atom™ E3827 (1.75 GHz) processor	4th Gen. Intel® Core™ i3-4010U/ i7-4650U (1.7 GHz) processor	SPC-1881WP: 4th Gen Intel® Core™ i3-4010U (1.7 GHz) processor SPC-2140WP: AMD® G-series T56N (1.6 G) processor	Intel® Celeron® J1900 processor	-	
<b>Memory</b>	4 GB of 1600 MHz DDR3L SODIMM SDRAM (8 GB optional)	4 GB of 1600 MHz DDR3L SODIMM SDRAM (8 GB optional)	4 GB of 1600 MHz DDR3L SODIMM SDRAM (8 GB optional)	4 GB of DDR3L SODIMM	4 GB of 1600 MHz DDR3L SODIMM SDRAM (8 GB optional)	-	
<b>Display</b>	<b>Display Type</b>	XGA TFT LED LCD	WXGA TFT LED LCD	SPC-1881WP: WXGA TFT LED LCD SPC-2140WP: Full HD TFT LED LCD	Full HD TFT LED LCD	FPM-7151W/7181W: WXGA TFT LED LCD FPM-7211W: Full HD TFT LED LCD	
	<b>Display Size</b>	TPC-1251T: 12.1" TPC-1551T: 15"	TPC-1051WP: 10.1" TPC-1551WP: 15.6"	TPC-1581WP: 15.6" TPC-1881WP: 18.5"	SPC-1881WP: 18.5" SPC-2140WP: 21.5"	21.5"	
	<b>Max. Resolution</b>	1024 x 768	TPC-1051WP: 1280 x 800 TPC-1551WP: 1366 x 768	TPC-1581WP: 1366 x 768 TPC-1881WP: 1367 x 768	SPC-1881WP: 1366 x 768 SPC-2140WP: 1920 x 1080	1920 x 1080	FPM-7151W/7181W: 1366 x 768 FPM-7211W: 1920 x 1080
	<b>Max. Colors</b>	TPC-1251T: 16.2M TPC-1551T: 16.7M	TPC-1051WP: 262K TPC-1551WP: 16.7M	16.7M			
	<b>Luminance (cd/m<sup>2</sup>)</b>	TPC-1251T: 600 nits TPC-1551T: 400 nits	300 nits				
	<b>Viewing Angle (H/V°)</b>	160/140	TPC-1051WP: 170/170 TPC-1551WP: 170/160	170/160	SPC-1881WP: 170/160 SPC-2140WP: 178/178	178/178	FPM-7151W/7181W: 170/160 FPM-7211W: 178/178
	<b>Backlight MTBF</b>	50,000 hrs	TPC-1051WP: 25,000 hrs TPC-1551WP: 50,000 hrs	50,000 hrs			
<b>Touchscreen</b>	5-wire resistive	Projected capacitive touch			Projected capacitive touch	Projected capacitive touch	
<b>Network (LAN)</b>	10/100/1000 Base-T x 2	10/100/1000 Base-T x 2		10/100/1000 Base-T x 2, M12 connector	10/100/1000 Mbps RJ45 x 2	-	
<b>Video Port</b>	-	HDMI		-	-	VGA & DVI/HDMI	
<b>I/O</b>	1 x RS-232, 1 x RS-232/422/485, 1 x USB 3.0, 1 x USB 2.0	1 x RS-232, 1 x RS-232/422/485, 1 x USB 3.0, 1 x USB 2.0	1 x RS-232/422/485, 1 x RS-232, 2 x USB 3.0, 1 x HDMI 1.4, 1 x Audio Out, 1 x USB 2.0 (optional), 1 x Audio Mic In (optional)	1 x RS-232, 1 x USB 2.0 to M12 connector, 1 24VDC to M12 connector, 1 x M12 connector	1 x RS-232, 1 x RS-232/485/422, 1 x USB 2.0, 1 x USB 3.0, 1 x waterproof wireless antenna (optional)	1 x RS-232/USB interface for touchscreen	
<b>HDD (Optional)</b>	2.5" SATA HDD	2.5" SATA HDD			2.5" SATA HDD	-	
<b>Intelligent Keys</b>	-	The function keys and home button built into the front panel enable quick access and configuration.			Yes	-	
<b>CompactFlash Slots</b>	1 x CFast	1 x CFast		-	1 x CFast	-	
<b>Expansion Slots</b>	1 x Full-size Mini PCIe	1 x Full-size Mini PCIe	1 x Full-size Mini PCIe (supports iDoor with the TPC-1251T-EHKE expansion kit)		1 x Full-size Mini PCIe	-	
<b>Input Power</b>	24V <sub>DC</sub> ± 20%			24V <sub>DC</sub>	24V <sub>DC</sub> ± 20%		
<b>Ingress Protection</b>	IP66-rated front panel	IP66-rated front panel		IP66-rated entire unit	IP69K-rated front panel IP69K-rated entire unit (optional)	IP66-rated front panel	
<b>Enclosure</b>	Front panel: Die-cast magnesium alloy Rear cover: SECC	Front panel: Die-cast magnesium alloy Rear cover: SECC	Front panel: Die-cast aluminum alloy Rear cover: PC/ABS resin	Front panel: Die-cast aluminum alloy Rear cover: Die-cast aluminum alloy	Front panel: Stainless steel Rear cover: Aluminum/stainless steel (optional)	Front panel: Die-cast magnesium alloy Rear cover: SECC	
<b>Mount Options</b>	Panel, desktop, wall, and VESA mount brackets (with optional mount kit)	Panel, desktop, wall, and VESA mount brackets (with optional mount kit)		Desktop, wall, and VESA arm mount brackets	VESA and flange adapter for arm and foot mount brackets	Desktop, wall, and VESA arm mount brackets	
<b>Operating Temperature</b>	-20 – 60 °C (-4 – 140 °F)	TPC-1051WP: -20 – 55 °C (-4 – 131 °F) TPC-1551WP: 0 – 55 °C (32 – 131 °F)	0 – 55 °C (32 – 131 °F)	0 – 55 °C (32 – 131 °F)	0 – 50 °C (32 – 122 °F)	0 – 55 °C (32 – 131 °F)	
<b>Storage Temperature</b>	-30 – 70 °C (-22 – 158 °F)	TPC-1051WP: -30 – 70 °C (-22 – 158 °F) TPC-1551WP: -20 – 60 °C (-4 – 140 °F)	-20 – 60 °C (-4 – 140 °F)	-20 – 60 °C (-4 – 140 °F)	-20 – 60 °C (-4 – 140 °F)		
<b>Dimensions (W x H x D)</b>	TPC-1251T: 311.80 x 238 x 57.2 mm (12.28 x 9.37 x 2.25") TPC-1551T: 383.2 x 307.3 x 61.1 mm (15.09 x 12.10 x 2.41")	TPC-1051WP: 283.1 x 202.3 x 61.4 mm (11.15 x 7.96 x 2.42") TPC-1551WP: 419.7 x 269 x 61.9 mm (16.52 x 10.59 x 2.44")	TPC-1581WP: 419.7 x 269 x 56.7 mm (16.52 x 10.59 x 2.23") TPC-1881WP: 488 x 309 x 56.7 mm (19.21 x 12.17 x 2.23")	SPC-1881WP: 488 x 309 x 65 mm (19.21 x 12.17 x 2.56") SPC-2140WP: 558.4 x 349.8 x 56.7 mm (21.98 x 13.77 x 2.23")	555 x 346.5 x 81 mm (21.85 x 13.64 x 3.19")	FPM-7151W: 419.7 x 269 x 47.7 mm (16.52 x 10.59 x 1.88") FPM-7181W: 488 x 309 x 47.7 mm (19.21 x 12.17 x 1.88") FPM-7211W: 558.4 x 349.8 x 47.7 mm (21.98 x 13.77 x 1.88")	
<b>Weight</b>	TPC-1251T: 2.5 kg (5.51 lbs) TPC-1551T: 3.9 kg (8.59 lbs)	TPC-1051WP: 2.56 kg (5.64 lbs) TPC-1551WP: 5 kg (11.02 lbs)	TPC-1581WP: 6 kg (13.22 lbs) TPC-1881WP: 7 kg (15.44 lbs)	SPC-1881WP: 8 kg (17.64 lbs) SPC-2140WP: 9 kg (19.8 lbs)	15.8 kg (34.76 lbs)	FPM-7151W: 5 kg (11 lbs) FPM-7181W: 6 kg (13.2 lbs) FPM-7211W: 8 kg (17.6 lbs)	
<b>Certification</b>	BSMI, CCC, CE, FCC Class A, UL						
<b>Operating System</b>	Microsoft® WEST/WE8S/Windows 7/8.1/10 Enterprise LTSS, Linux	Microsoft® WEST/WE8S/Windows 7/8.1/10 Enterprise LTSS, Linux			Microsoft® WEST (32/64 bit), Windows 7 (32/64 bit), Windows Embedded 8.1 Industry Pro (64 bit)	Microsoft® XP/Vista/7/8/10/XPe, CE, Linux	

# Advantech's Innovative Design Concept - Simple, Flexible, and Reliable

As a leading provider of industrial PCs, Advantech is committed to continual product innovation and service development. Advantech's pioneering intelligent automation "i" technology concept emphasizes intelligent, integrated, and intuitive designs that innovate existing service models, user behaviors, and technology trends for the new era of industrial automation.



The integration of an intuitive and intelligent key simplifies automation panel configuration, while the flexible software design ensures easy and convenient customization.



This standardized modular interface enables flexible expansion by supporting numerous applications and extended system functions through a wide range of I/O.



This reliable long-distance transmission technology transfers video signals and touch control commands over a single Ethernet cable, overcoming the inherent interference of harsh environments to ensure connectivity and provide a cost effective multi-display solution.

## Regional Service & Customization Centers

**China** | Kunshan  
86-512-5777-5666

**Taiwan** | Taipei  
886-2-2792-7818

**Netherlands** | Eindhoven  
31-40-267-7000

**Poland** | Warsaw  
00800-2426-8080

**USA** | Milpitas, CA  
1-408-519-3898

## Worldwide Offices

### Greater China

**China**  
Toll Free 800-810-0345  
Beijing 86-10-6298-4346  
Shanghai 86-21-3632-1616  
Shenzhen 86-755-8212-4222  
Chengdu 86-28-8545-0198  
Hong Kong 852-2720-5118

**Taiwan**  
Toll Free 0800-777-111  
Neihu 886-2-2792-7818  
Xindian 886-2-2218-4567  
Taichung 886-4-2329-0371  
Kaohsiung 886-7-229-3600

### Asia Pacific

**Japan**  
Toll Free 0800-500-1055  
Tokyo 81-3-6802-1021  
Osaka 81-6-6267-1887  
Nagoya 81-52-856-9657

**Korea**  
Toll Free 080-363-9494  
Seoul 82-2-3663-9494

**Singapore**  
Singapore 65-6442-1000

**Malaysia**  
Kuala Lumpur 60-3-7725-4188  
Penang 60-4-537-9188

**Thailand**  
Bangkok 66-2-248-3140

**India**  
Bangalore 91-80-2545-0206  
Pune 91-20-3948-2075

**Indonesia**  
Jakarta 62-21-751-1939

**Australia**  
Toll Free 1300-308-531  
Melbourne 61-3-9797-0100  
Sydney 61-2-9476-9300

### Europe

**Germany**  
Toll Free 00800-2426-8080/81  
Munich 49-89-12599-0  
Düsseldorf 49-2103-97-855-0

**France**  
Paris 33-1-4119-4666

**Italy**  
Milano 39-02-9544-961

**Benelux & Nordics**  
Breda 31-76-523-3100

**UK**  
Newcastle 44-0-191-262-4844  
London 44-0-870-493-1433

**Poland**  
Warsaw 48-22-31-51-100

**Russia**  
Moscow 8-800-555-01-50  
St. Petersburg 8-800-555-81-20

**Czech Republi**  
Ústí nad Orlicí 420-465-521-020

**Ireland**  
Oranmore 353-91-792444

### Americas

**North America**  
Toll Free 1-888-576-9668  
Cincinnati 1-513-742-8895  
Milpitas 1-408-519-3898  
Irvine 1-949-420-2500  
Ottawa 1-815-434-8731

**Brazil**  
Toll Free 0800-770-5355  
São Paulo 55-11-5592-5355

**Mexico**  
Toll Free 1-800-467-2415  
Mexico City 52-55-6275-2727

**ADVANTECH**

Enabling an Intelligent Planet

<http://www.advantech.com>

Please verify specifications before quoting. This guide is intended for reference purposes only. All product specifications are subject to change without notice.

No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher.

All brand and product names are trademarks or registered trademarks of their respective companies. © Advantech Co., Ltd. 2016

More Information



860000150