

# ECU-4784

## Intel IEC-61850-3 Certified Power Automation Computers

NEW



### Features

- Intel 6th Gen i5-6300U Processor
- DDR3L RAM 16G, up to 32G
- Isolated 8 x LAN, 10 x Serial Port Communication Interfaces
- 100-240 V<sub>DC</sub>/V<sub>AC</sub> Power Supply
- 2 x IO Expansion Slots
- 3 x 2.5" SATA HDD, 1 x m.2 PCIE
- DVI-I, DVI-D Display Interface
- Programmable LEDs
- Remote Management
- Trusted Platform Module (TPM2.0)
- Virtualization Technology for Directed I/O

### Introduction

The ECU-4784 series are TUV IEC 61850-3 and IEEE 1613-certified products that provide high reliability and stability for power automation applications. The fanless robust design, high CPU performance, flexible expansion, rich communication interfaces, and intelligent functions make the ECU-4784 series of industrial PCs suitable to serve as smart substations in harsh environments.

### Specifications

#### General

- **Certification** CE, FCC, CCC, Electricity IV level for China, IEC-61850-3, IEEE-1613, UL, CB, LVD
- **Power Requirements** Power Supply  
Power1: 100 ~ 240 V<sub>AC</sub>, 100 ~ 240 V<sub>DC</sub> (Inside)  
Power2: 100 ~ 240 V<sub>AC</sub>, 100 ~ 240 V<sub>DC</sub> (option)
- **Power Consumption** 52.8W with full loading on CPU, memory, COM, LAN
- **Operating System** Windows10, Windows Server 2019, Linux
- **Dimensions (W x D x H)** 440 x 280 x 88 mm
- **Enclosure** SECC and aluminum
- **Weight** 6.0 Kg
- **Mounting** 2U Rackmount
- **System Design** Fanless

#### System Hardware

- **CPU** Intel 6th Gen i5-6300U
- **Memory** DDR3L 16G, up to 32G
- **Indicators** LEDs for PWR1, PWR2, HDD, LAN (LINK, ACT), COM (TX, RX), Slot 1, and Slot 2, Programmable
- **Storage** 3 x 2.5" SATA HDD  
1 x m.2 PCIE  
HDD Height less than 11mm
- **Display** 1 x DVI-I, 1 x DVI-D (Resolution: 1920 x 1080)
- **Watchdog Timer** Programmable 256 levels time interval, from 1 to 255 seconds for each tier
- **Relay Relay** Output Form C  
Contact 5A @ 125V<sub>AC</sub>/ 5A @ 30V<sub>DC</sub>  
Channel 1

#### Communication Interface

- **Serial Ports** 2 x RS-232 (DB9 connectors, Standard)  
8 x RS-232/422/485 (Terminal Block)  
2,500V isolation
- **Serial Port Speed** RS-232: 50 ~ 115.2 kbps  
RS-422/485: 50 ~ 921.6 kbps (Max.)
- **LAN** 8 x 10/100/1000 Base-T RJ45 ports  
(Supports teaming function, PXE, LAN1 supports AMT)
- **USB** 4 x USB, UHCI, rev 2.0 compliant (3 x rear, 1 x internal)  
2 x USB, UHCI, rev 3.0 compliant (2 x front)
- **Expansion** 2 x Domain I/O expansion slots  
(Each slot supports 1 x PCIe and 2 x PCI)

#### Environment

- **Operating Temperature** -25 ~ 70°C (-13 ~ 158°F)  
IEC 60068-2-2 with 100% CPU/ I/O loading, 24 hrs
- **Operating Humidity** 5 ~ 95% RH (non-condensing)
- **Storage Humidity** 5 ~ 95% RH (non-condensing)
- **Shock Protection** IEC 68 2-27: 30 G, 11 ms
- **Vibration Protection** IEC 68-2-64: 2G, Sine, 5 ~ 500 Hz

### Ordering Information

- **ECU-4784-E36SCE** Intel 6th Gen i5-6300U processor with 16 GB RAM, 8 x LAN, 10 x COM, 2 x expansion slots
- **ECU-4784-E36SCU** AC/DC 100 ~ 240V, 150W, W/PFC
- **XECU-FSP150-1H35 (\*)** (Note: Dual power configuration is available upon request via Advantech CTOS)
- **9893SW0400E (\*)** DC 36V ~ 72V module  
(Note: A 48V power module is available upon request via Advantech CTOS)