





Industrial Wireless

	4G Terminal	3G Terminal	3G Terminal	2G Terminal
Model Name	IS-C4100	IS-C3100	IS-C3050	IS-C2050
Basic Selection				
Product Photo				
2G/GPRS/GSM, Multi-slot class 12(quad band) Mobile station Class B	●	●	●	●
EU GSM/GPRS/EDGE : 900/1800 MHz and UMTS / HSPA+ : 900/2100	●	●	●	
US GSM/GPRS/EDGE : 850/1900 MHz and UMTS/ HSPA+ : 850/1900 MHz	●	●	●	
4G LTE, B1-B5, B7, B12, B13, B17, B20, B25, B26, B29, B30, B41	●			
WCDMA, B1, B2, B3, B4, B5, B8	●			
Operation mode, Transparent(TCP Server/ TCP Client/ UDP mode)	●	●	●	●
Operation mode, CCP Control(TCP/UDP), SMS/AT command	●	●	●	●
10/100Mb TX	2	1		
RS232/422/485 Module			1	1
SIM card slot	2	1	1	1
Data Buffering	●	●	●	
Redundant Power Input	5~32V DC	5~32V DC	5~32V DC	5~32V DC
DC jack connector	●	●	●	●
Protocol				
TCP/IP	●	●		
Serial			●	●
Hardware Features				
Din-Rail / Wall mount	●	●	●	●
Reverse Power protection	●	●	●	●
-40~85°C Operating temperature	●	●	●	●
CE	●	●	●	●
Power Consumption	Max. 4Watt	Max. 4Watt	Max. 4Watt	Max. 4Watt
Relay output (Normal Open)	1A. 24V	1A. 24V	1A. 24V	1A. 24V
Package Information				
Dimension(LxWxD) mm	TBD	119.5 x 89 x 26.9	119.5 x 89 x 26.9	119.5 x 89 x 26.9
Weight (w / o packing case)	TBD	200g	200g	200g