


PCA-6028

LGA1150 Intel® Core™ i7/i5/i3/Pentium SBC with VGA/DVI/Dual GbE LAN

NEW



Features

- Supports Intel® Core™ i7/i5/i3/Pentium LGA1150 processors with H81
- Dual Channel (Non-ECC) DDR3 1333/1600 up to 16 GB
- Supports USB 3.0, SATA3.0
- Dual display with VGA and DVID-D (optional)
- Supports Advantech LPC modules.
- Supports SUSIAccess and Embedded Software APIs

Software APIs:




Utilities:



Specifications

Processor System	CPU	i7-4770S	i7-4770TE	i5-4570S	i5-4570TE	i3-4330	i3-4330TE	G3420	G3320TE
	Base Frequency	3.1GHz	2.3GHz	2.9GHz	2.7GHz	3.5GHz	2.4GHz	3.2GHz	2.3GHz
	L3 Cache	8MB	8M	6MB	4MB	4MB	3MB	3MB	3MB
	SKU/Chipset	Intel H81							
Bus	BIOS	AMI 128Mbit SPI Flash							
	ISA	HISA (ISA High Driver)							
Memory	PCI	32 bit/ 33 MHz PCI							
	Technology	Dual channel (Non-ECC) DDR3 1333/1600							
	Max. Cap.	16 GB (8 GB per DIMM)							
Graphics	Socket	DDR3 240-pin DIMM x 2							
	Controller	Chipset integrated Intel HD Graphics							
	VRAM	Shared system memory is subject to OS							
	CRT	Supports resolution up to 2048 x 1536 pixel at 60Hz							
Ethernet	DVI-D	Supports resolution up to 1920 x 1200 pixel at 60Hz (G2 only)							
	Interface	10/100/1000 Mbps							
	Controller	LAN 1: Intel I217V LAN 2: Intel I211 (Only in G2 Sku)							
SATA	Connector with LED	RJ45 x 1 (VG sku); RJ45 x 2(G2 sku)							
	Channel	SATA 3.0 x 2 (600 MB/sec), SATA2.0 x 2 (300MB/sec)							
Rear I/O	USB 2.0	1 (Only in G2 sku)							
	Ethernet	1 (VG sku); 2 (G2 sku)							
	VGA	1							
	PS/2	1 (PS/2 Y cable supports 1 x keyboard and 1 x mouse)							
Internal Connector	USB	Up to 8x USB2.0 (6x Pin header, 1x Type A, 1x Rear in G2 sku only) 2x USB3.0 (Pin header)							
	SATA	4(1x SATA2.0, 2x SATA3.0, 1x mSATA)							
	DVI-D	1 (Pin header)							
	COM	2							
	Parallel	1							
	IrDA	1							
	GPIO	8-bit							
Watchdog Timer	Output	System reset							
	Interval	Programmable 1-255 sec							
Miscellaneous	Audio	Intel High Definition audio interface (required an audio extension module P/N: PCA-AUDIO-HDA1E)							
Power Requirement	Test Environment	Core i5-4670S CPU@3.10GHz+DDR3-1066*2+SATA HDD*1							
	Voltage	+12V	+5V	+3.3V	+5Vsb	-12V	-5V		
	Current	0.32A	1.92A	0A	0.06A	0A	0A		
Environment	Operating								Non-operating
	Temperature/Humidity	0 ~ 60° C(32~140° F); Depends on CPU frequency and cooler solution						-40 ~ 85° C and 60° C @ 95% RH Non-Condensing	
Physical	Dimensions	338 mm (L) x 122 mm (W) (13.3" x 4.8")							

Block Diagram



Ordering Information

Part Number	LAN	VGA	DVI-D	COM	SATA	USB	m-SATA
PCA-6028VG-00A1E	1	Yes	-	2	3 (1 x 2.0 + 2 x 3.0)	9 (2 x 3.0 + 7 x 2.0)	1
PCA-6028G2-00A1E	2	Yes	1*	2	3 (1 x 2.0 + 2 x 3.0)	10 (2 x 3.0 + 8 x 2.0)	1

*Note: Output DVI-D signal only (Required DVI-D cable: 1700021831-01)

Optional Accessories

Part Number	Description
1960047831N001	PCA-6028 optimized CPU Cooler (2U)
PCA-AUDIO-HDA1E	Audio module
PCA-TPM-00A1E	TPM module(Trust Platform management)
1700020277-01	2 ports USB 3.0 cable W/ BKT(30cm)
1700021831-01	DP to DVI-D cable w/ BKT

Packing List

Part Number	Description	Quantity
1700003194	Serial ATA HDD data cable	x2
1703150102	Serial ATA HDD power cable	x2
1701260305	COM + printer ports cable kit	x1
1700060202	Keyboard and mouse Y-cable	x1
1700008461	4-port USB cable kit	x1
9689000068	Jumper package	x1
2190000902	Warranty Card	x1
2006602800	Startup manual	x1
2066602800	Utility CD	x1

Bracket View



PCA-6028G2-00A1E



PCA-6028VG-00A1E